



(19)

60105507 A

(11) Publication number:

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: 58213847

(51) Intl. Cl.: B29C 39/24

(22) Application date: 14.11.83

(30) Priority:

(43) Date of application
publication: 11.06.85(84) Designated contracting
states:

(71) Applicant: TOKYO SEAT KK

(72) Inventor: MIYAZAKI MASAHIRO
SHIBATA TAMOTSU
YOSHIMURA HITOO

(74) Representative:

**(54) PREPARATION OF
INTEGRALLY BLOW-
MOLDED PIECE**

(57) Abstract:

PURPOSE: To prepare voidfree pad material by a method wherein resin flow in a blow mold is adjusted by a porous baffle plate and the corner sides of a mold cover member.

CONSTITUTION: The porous baffle plate 5 with networks 5a... is inserted previously into the cover member 1. Foam material is injected gradually

into the cover member 1 and expanded. Then, the flow of the foam material is moved forcibly by the porous baffle plate 5 toward the corner part 3a of the rise part. Stagnant expanded gas is extruded by this forced adjustment not to produce voids 4'. In this manner, the pad material 4 free from defects such as voids etc. can be provided.

COPYRIGHT: (C)1985,JPO&Japio

